

# AC Level 2 70A SINGLE PORT CHARGING STATION (PEDESTAL)

MODEL	SINGLE PORT 70A L2P-70-240-16-001
Power per Port	16.8 kW (240 VAC @ 70A)
ELECTRICAL SERVICE	
Power	240/208 VAC, 70A Load with 100A Branch Circuit Per Port
Service Panel	100A Breakers per Port (No GFCI)
Service Wiring	3-Wire (L1, L2, Earth Ground)
FUNCTIONAL INTERFACES	
Connector Type	SAE J1772
Charging Protocol	SAE J1772
Standard Cable Length	25 ft
Cable Retractor	Optional (Cable 18 ft w/ Cable Management)
LCD Display	1000 Nits, 7" Color, 800 x 480, UV Protected
Card Reader	ISO 14443 Type A & B, ISO 18092 NFC
SAFETY AND CONNECTIVITY	
Ground Fault Detection	20 mA
Plug-Out Detection	SAE J1772
Power Measurement (opt)	Accuracy: ± 1% from 5% to Full Scale (70A)
Power Report Interval	Every 15 minute on the hour
Wireless	2.4 GHz Wi-Fi (802.11 b/g/n)
Wide Area Network	4G Modem
Communication Protocols	OCPP 1.5 and 1.6 Compliant
SAFETY AND OPERATION	
Enclosure Rating	NEMA 3R
Regulatory Compliance	ETL Certified for USA and cUL Certified for Canada; Complies with UL 2594, UL 2231-1, UL 2231-2, and NEC Article 625, EMC: FCC Part 15 Class A
Operating Temperature	-20°C to +60°C (-4°F to 140°F)
Storage Temperature	-50°C to +80°C (-58°F to 176°F)
Humidity	95% Non-Condensing

- ▶ SINGLE PORT 70A LEVEL 2
- ▶ CHARGING PROTOCOL: SAE J1772
- ▶ 16.8 KW PER PORT
- ▶ 25 FT or 18 FT with CABLE RETRACTOR
- ▶ NEMA 3R HOUSING
- ▶ RFID READER
- ▶ OCPP COMPLIANT – STANDARD
- ▶ 7" COLOR SCREEN – STANDARD
- ▶ UL COMPLIANT – ETL CERTIFIED
- ▶ OPTIONS:
  - CABLE RETRACTOR
  - CREDIT CARD READER
  - CREDIT CARD SCANNER

